

Created on: 03-07-2024 09:22:05 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltru®: Chemical container type STI 4000 (ISO)



Size Chemical container type STI 4000 (ISO)

Article number	5085
External dimensions LxWxH	5080 x 4340 x 2520 mm
Dimensions internal LxWxH	4860 x 4100 x 2200 mm
Load capacity of slatted floor	1000 kg/m ²
Collection box	Galvanised steel 3 mm with galvanised gratings
Contents collection box	2x 1480 litres
Weight	2742 kg
Door	Lockable, WxH=1200 x 2100 mm
Underride height modules	100 mm

Specifications Chemical container type STI 4000 (ISO)

[Chemical containers ISO modular:](#)

Certification:

- Designed as a non-fireproof storage container in accordance with the directive PGS 15.
- General approval of the German Institute of Building Technology, DIBt Berlin.

Housing:

- Door, walls and roof manufactured from a hot-dip galvanised sandwich panel with sheet piling in colour RAL 9002/white .
- Sandwich panel made of galvanised sheet with core of environmentally friendly and insulating polyurethane rigid foam, insulation value 0.47 W/m²K.
- The roof is fitted with an integrated rain gutter at the front and rear.
- Maximum roof load (snow load) 100 kg/m².
- Maximum wind load on the walls: w = 0.40 KN/m².
- Maximum wind suction on roof and walls: w = -0,25 KN/m².

Door:

- In the long or short provided with a single wing door 1200x2100 mm side with latch on inside and outside, panic lock on inside and lockable with a cylinder lock.

Drip tray:

- Hot dip galvanised liquid tight uninsulated drip tray manufactured from 3 mm steel plate S235JR with removable galvanised grid floor.
- Maximum floor load 1000 kg/m² with evenly distributed load.
- Sump with liquid-tightness certificate issued by TÜV Rheinland e.V.

Hazard identification:

- Hazard indication by pictograms in accordance with PGS 15.

Installation/delivery:

- The individual modules are delivered (pre-)assembled and assembled at your site.