

Created on: 03-07-2024 09:34:50 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Chemical container type CC 6-XL (ISO)

Size Chemical container type CC 6-XL (ISO)

Article number	600330250
External dimensions LxWxH	6010 x 2540 x 2610 mm
Dimensions internal LxWxH	5730 x 2180 x 2300 mm
Load capacity of slatted floor	1475 kg/m ²
Collection box	Steel lacquered with galvanized gratings
Contents collection box	965 litres
Weight	2300 kg
Door	Lockable, B=1800 mm

Specifications Chemical container type CC 6-XL (ISO)[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m²K).

Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m² with evenly distributed load.

Ventilation:

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

Miscellaneous:

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.