

Created on: 03-04-2025 05:35:08 |  
 Technical changes and imperfections reserved.

**PRODUCT DATA SHEET Hiltra®: Chemical container type CC 1-25 (ISO)**



Size Chemical container type CC 1-25 (ISO)

Article number	200150100+200150107
External dimensions LxWxH	1420 x 1440 x 2275 mm
Dimensions internal LxWxH	1165 x 1105 x 1850 mm
Grid floor load capacity	500 kg/m2
Tray	Steel, blasted and finished with 100 mu Acraton/RAL7005 (mouse gray) with galvanized gratings
Contents collection container	220 liters
Weight	415 kg
Door opening size (WxH)	Lockable, WxH : 1300 x 1890 mm

**Specifications Chemical container type CC 1-25 (ISO)**

[Chemical containers thermally insulated:](#)

**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m2K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltra®: Chemical container type CC 1 (ISO)



### Size Chemical container type CC 1 (ISO)

Article number	210110100-210110219
External dimensions LxWxH	2090 x 1140 x 2250 mm
Dimensions internal LxWxH	1830 x 800 x 1880 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	220 litres
Weight	400 kg
Door	Lockable, B=1300 mm (shown B=1800 mm)

### Specifications Chemical container type CC 1 (ISO)

#### [Chemical containers thermally insulated:](#)

#### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

#### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

#### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

#### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 2 (ISO)



Size Chemical container type CC 2 (ISO)

Article number	300230200-300220409
External dimensions LxWxH	2090 x 2170 x 2250 mm
Dimensions internal LxWxH	1810 x 1810 x 1940 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	250 litres
Weight	710 kg
Door	Lockable, B=1300 mm

### Specifications Chemical container type CC 2 (ISO)

#### [Chemical containers thermally insulated:](#)

##### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

##### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value 0.47 W/m<sup>2</sup>K).

##### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

##### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80

µm two-component zinc phosphate coating in RAL 7040/ window grey.

- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 2-L (ISO)



Size Chemical container type CC 2-L (ISO)

Article number	200330200-200220419
External dimensions LxWxH	2090 x 2170 x 2610 mm
Dimensions internal LxWxH	1810 x 1810 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	250 litres
Weight	810 kg
Door	Lockable, B=1800 mm

### Specifications Chemical container type CC 2-L (ISO)

[Chemical containers thermally insulated:](#)

#### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

#### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

#### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

#### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80

µm two-component zinc phosphate coating in RAL 7040/ window grey.

- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.



Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 2-XL (ISO)



Size Chemical container type CC 2-XL (ISO)

Article number	200330250-200220429
External dimensions LxWxH	2170x 2460 x 2610 mm
Dimensions internal LxWxH	1810 x 2180 x 2300 mm
Load capacity of slatted floor	1475 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	295 litres
Weight	990 kg
Door	Lockable, B=1800 mm

### Specifications Chemical container type CC 2-XL (ISO)

[Chemical containers thermally insulated:](#)

#### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

#### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

#### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

#### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80

µm two-component zinc phosphate coating in RAL 7040/ window grey.

- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 3 (ISO)



Size Chemical container type CC 3 (ISO)

Article number	300230200
External dimensions LxWxH	3010 x 2170 x 2250 mm
Dimensions internal LxWxH	2730 x 1810 x 1940 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	380 litres
Weight	980 litres
Door	Lockable, B=1300 mm

### Specifications Chemical container type CC 3 (ISO)

#### [Chemical containers thermally insulated:](#)

##### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

##### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

##### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

##### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 3-L (ISO)



Size Chemical container type CC 3-L (ISO)

Article number	300330200
External dimensions LxWxH	3010 x 2170 x 2610 mm
Dimensions internal LxWxH	2730 x 1810 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	380 kg
Weight	1070 kg
Door	Lockable, B=1800 mm

### Specifications Chemical container type CC 3-L (ISO)

#### [Chemical containers thermally insulated:](#)

#### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

#### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

#### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

#### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 3-XL (ISO)



Size Chemical container type CC 3-XL (ISO)

Article number	300330250
External dimensions LxWxH	3010 x 2540 x 2610 mm
Dimensions internal LxWxH	2730 x 2180 x 2300 mm
Load capacity of slatted floor	1475 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	455 litres
Weight	1290 kg
Door	Lockable, B=1800 mm

### Specifications Chemical container type CC 3-XL (ISO)

#### [Chemical containers thermally insulated:](#)

##### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

##### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

##### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

##### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.



Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container type CC 4 (ISO)**

Size Chemical container type CC 4 (ISO)

Article number	400230200
External dimensions LxWxH	4050 x 2170 x 2250 mm
Dimensions internal LxWxH	3770 x 1810 x 1940 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Painted steel, W=1300 mm
Contents collection box	525 litres
Weight	1280 litres
Door	Lockable, B=1300 mm

**Specifications Chemical container type CC 4 (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

## PRODUCT DATA SHEET Hiltra®: Chemical container type CC 4-L (ISO)



Size Chemical container type CC 4-L (ISO)

Article number	400330200
External dimensions LxWxH	4050 x 2170 x 2610 mm
Dimensions internal LxWxH	3770 x 1810 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized grid floor
Contents collection box	525 litres
Weight	1350 kg
Door	Lockable, B=1800 mm

### Specifications Chemical container type CC 4-L (ISO)

#### [Chemical containers thermally insulated:](#)

##### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

##### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

##### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

##### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
 Technical changes and imperfections reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container type CC 4-XL (ISO)**



Size Chemical container type CC 4-XL (ISO)

Article number	400330250
External dimensions LxWxH	4050 x 2540 x 2610 mm
Dimensions internal LxWxH	3770 x 2180 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized grid floor
Contents collection box	630 litres
Weight	1620 kg
Door	Lockable, B=1800 mm

**Specifications Chemical container type CC 4-XL (ISO)**

[Chemical containers thermally insulated:](#)

**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltru®: Chemical container type CC 5 (ISO)



Size Chemical container type CC 5 (ISO)

Article number	500230200
External dimensions LxWxH	5090 x 2170 x 2250 mm
Dimensions internal LxWxH	4810 x 1810 x 1940 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	665 litres
Weight	1570 kg
Door	Lockable, B=1300 mm

### Specifications Chemical container type CC 5 (ISO)

#### [Chemical containers thermally insulated:](#)

##### Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

##### Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

##### Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

##### Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.



Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container CC 5-L (ISO)**

Size Chemical container CC 5-L (ISO)

Article number	500330200
External dimensions LxWxH	5090 x 2170 x 2610 mm
Dimensions internal LxWxH	4810 x 1810 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	665 litres
Weight	1640 kg
Door	Lockable, B=1800 mm

**Specifications Chemical container CC 5-L (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container type CC 5-XL (ISO)**

Size Chemical container type CC 5-XL (ISO)

Article number	500330250
External dimensions LxWxH	5090 x 2540 x 2610 mm
Dimensions internal LxWxH	4810 x 2180 x 2300 mm
Load capacity of slatted floor	1475 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	800 litres
Weight	1960 kg
Door	Lockable, B=1800 mm

**Specifications Chemical container type CC 5-XL (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltra®: Chemical container type CC 6 (ISO)**

## Size Chemical container type CC 6 (ISO)

Article number	600230200
External dimensions LxWxH	6010 x 2170 x 2250 mm
Dimensions internal LxWxH	5730 x 1810 x 1940 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	800 litres
Weight	1850 kg
Door	Lockable, B=1300 mm (shown B=1800 mm)

**Specifications Chemical container type CC 6 (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.

- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.

Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container type CC 6-L (ISO)**

Size Chemical container type CC 6-L (ISO)

Article number	600330200
External dimensions LxWxH	6010 x 2170 x 2610 mm
Dimensions internal LxWxH	5730 x 1810 x 2300 mm
Load capacity of slatted floor	1300 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	800 litres
Weight	1890 kg
Door	Lockable, B=1800 mm

**Specifications Chemical container type CC 6-L (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.



Created on: 03-04-2025 05:35:08 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemical container type CC 6-XL (ISO)**

Size Chemical container type CC 6-XL (ISO)

Article number	600330250
External dimensions LxWxH	6010 x 2540 x 2610 mm
Dimensions internal LxWxH	5730 x 2180 x 2300 mm
Load capacity of slatted floor	1475 kg/m <sup>2</sup>
Collection box	Steel lacquered with galvanized gratings
Contents collection box	965 litres
Weight	2300 kg
Door	Lockable, B=1800 mm

**Specifications Chemical container type CC 6-XL (ISO)**[Chemical containers thermally insulated:](#)**Outer casing:**

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanized sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.

**Insulation:**

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m<sup>2</sup>K).

**Doors:**

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

**Drip tray:**

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity

1000 kg/m<sup>2</sup> with evenly distributed load.

**Ventilation:**

- Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

**Miscellaneous:**

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.