

Created on: 28-12-2024 12:48:49 |  
 Technical changes and imperfections reserved.

**PRODUCT DATA SHEET Hiltra®: Megasaver F60 model MS603425**



Size Megasaver F60 model MS603425

Article number	600500500
External dimensions LxWxH	approx. 6033 x 3443 x 2610 mm
Dimensions internal LxWxH	approx. 5840 x 3250 x 2240 mm
Net daylight size single door WxH	approx. 1045 x 2085 mm (when opened to 90 degrees)
Collection capacity	approx. 2890 litres
Weight	approx. 3420 kg
Fire resistance (F60)	Efectis report (whole unit): 2016-Efectis-R000221[Rev.1]/GHJ/TNL

**Specifications Megasaver F60 model MS603425**

Version (abridged) 1.3 - 23-5-2019

[HILTRA® MEGASAVER®:](#)

**Design/fire resistance:**

- The composite structure has been assessed by the accredited testing institute EFECTIS®.
- Efectis report , no: 2016-Efectis-R000221[Rev.1]/GHJ/TNL valid until 31.03.2021.
- Designed as an independent fire compartment for the storage of packaged hazardous substances based on PGS 15:2016 Version 1.0.
- Fire resistance of 60 minutes determined in case of a fire from outside and a fire from inside on all (for the chosen use applicable) criteria of PGS 15:2016 Version 1.0, Regulation 3.2.9.

**Main supporting structure:**

- Welded, steel main supporting structure based on a structural strength calculation (for the chosen deployment) according to the Building Code and the aforementioned European and Dutch standards for steel structures:
- Steel structure manufactured from blank steel, degreased and provided with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.
- Fire resistance on "failure" criterion (R-60 for main support structures).

**Enclosure:**

- Roof and walls in lightly profiled galvanised sandwich panels with a core made of non-combustible and insulating rock wool.
- Insulation value [W/m<sup>2</sup>K]: 0.47 (according to EN ISO 6946).
- Sound insulation value (through air)  $R_w$  (C: Ctr): 32 dB .
- Colour outside; a Myrialac® primer and polyester coating in RAL 7035/grey.
- Colour inside; a Myrialac® primer and polyester coating in RAL 9002/white.
- Fire resistance of the sandwich panels = 60 minutes in accordance with: NEN 6069: 2011, Test standards EN 1363-1 & 1364-1 (EI-60 for walls), Test standards EN 1364-2 (RE-60 for ceilings/roofs), Classification standard: EN 13501-2.

**Door:**

- Equipped with a single, self-closing, right-hand hinged wing door in the short side.
- Door made of double-walled galvanised sheet with a core of non-flammable and insulating material.
- Door leaf finished on inside and outside in RAL 7005/mouse grey.
- Door provided with handle, panic bar, cylinder lock and door closer including automatic Thermolock fire resistant locking mechanism.
- Door rebate areas are provided with foam sealing strips so that they automatically close in case of fire.
- Door can be locked in an opening angle of approx. 90°, in case of fire the Thermolock breaks the lock and the door will close automatically in the latch (fire closing mechanism based on door hold open magnets in combination with detection and fire alarm control unit possible on request).
- Fire resistance of the door EI-1-60 minutes in accordance with: Test standard: EN 1364-1, Classification standard: EN 13501-2, Insulation value W/m<sup>2</sup>K: 1,1 (according to EN 14351-1/A1:2010), Sound insulation value (through air)  $R_w$  (C: Ctr): 32 dB (according to EN ISO 140-3).

**Drip tray:**

- Completely liquid-tight drip tray welded into the base frame made of steel sheet degreased and coated with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.
- Base frame fitted with removable, galvanised grid floor sections, type R2.30/30x60 mm with a load-bearing capacity of up to 1000 kg/m<sup>2</sup> with evenly distributed load (other grid types and floor loads on request).

**Ventilation openings:**

- Ventilation and de-aeration through diametrically arranged ventilation openings inside and outside finished with galvanised blade grilles.
- Standard equipped with flame retardant mesh and fire resistant louvres, so that they are automatically closed in case of fire.

**Hazard indication:**

- By pictograms in accordance with PGS 15, Ø and/or ? 200 mm, symbols: "smoking and open fire prohibited" and "flammable (liquid) materials" (other pictograms and signs available on request).

**Construction options:**

- Option A2: exterior finished in a different colour (instead of RAL 7035/light grey)

- Option B: Drip tray/structure SA2.5 blasted and finished with 100 µm Acreton zinc phosphate epoxy coating in RAL 7005/mouse grey.
- Option D1: instead of a single door, a double-leaf fire door.
- Option D2: Additional single self-closing door.
- Option D3: Additional double-leaf fire door.
- Option DB: weatherproof PVC roof membrane (for outside installations)
- Option F: flange ØxH=80x40 mm mounted in the roof or side panel for connecting a ventilation duct to the outside air.
- Option G: drip tray additionally provided on the inside with a reinforced, fibreglass-reinforced polyester lining to protect the drip tray(s) against the effects of chemicals. Resistance list on request.
- Option W: fire-resistant partition wall for compartmentalising incompatible hazardous substances combinations.

### Optional

Option description	Option article number
D1: Double door B=1500 mm instead of single door	300400150
D2: Extra single door B=1000 mm	300400151
D3: Extra double door B=1500 mm	300400152
W: F60 fire resistant partition wall for MS-xx3425	300400158