


Created on: 03-07-2024 09:46:38 |
 Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltru®: Hiltru F60 gas bottle depot model GD-MSP1-KA (CB F0)



Size Hiltru F60 gas bottle depot model GD-MSP1-KA (CB F0)

Article number	300150252
Dimensions uitw. WxDxH	± 2870 x 2420 x 2675 mm
Dimensions int. WxDxH	± 2430 x 2000 x 2460 mm
Door leaf size WxH	± 2420 x 2460 mm
Door	Lockable galvanised steel mesh door
Implementation of walls and roof	60 minutes fire resistant according to NEN 6069
Steel construction	with structural strength calculation
Weight	± 980 kg
Capacity	1x gas bottle pack (16x 50 liter standard cylinder)
Application	Storage and tipper handling

Specifications Hiltru F60 gas bottle depot model GD-MSP1-KA (CB F0)

Suitable for the storage of gas cylinders and gas cylinder packages. The gas cylinder depots are 60 minutes fire resistant in accordance with NEN 6069 and available with galvanised wire mesh doors or F60 fire doors. The products shown can be used within the PGS 15 regulations.

Features:

- Fire resistance of side walls, roof and door(s) 60 minutes in accordance with NEN 6069.
- Housing made of galvanized sandwich panels, polyester coated in RAL7035/light grey. Other colours on request.
- Optional wire mesh door(s) or F60 fire door(s).
- Mesh door(s) with handle and cylinder lock.
- F60 door(s) equipped with handle, panic handle, cylinder lock and automatic Thermolock firebreak technology.
- Door rebates are provided with sealing strips in case of fire so that they are automatically closed in case of fire.
- Standard without floor and threshold, which makes it easy to put in and take out gas bottles.
- Ventilation and de-aeration through diametrically arranged ventilation openings with flame-resistant and fire-resistant louvres.

- Hazard identification by means of pictograms in accordance with ISO3864: "Gas bottle hazard" and "Fire, naked flame and smoking prohibited".
- Optionally available fire resistant partition wall in the GD-MSP 2 models.
- Optionally available in F90 and F120 version.